



ELECTRICAL SPECIFICATIONS

ENCLOSURE STYLE: NEMA 3R, AIR COOLED, FLOOR MOUNT, DRY TYPE,
 GENERAL PURPOSE TRANSFORMER
 PRIMARY VOLTAGE: 240 X 480 VOLTS. 1 PH
 PRIMARY TAPS: 2-2 1/2%FCAN,4-2 1/2%FCBN
 FREQUENCY:60 HZ
 SECONDARY VOLTAGE: 120/240 VOLTS
 SHIELD: EARTH METAL SCREEN PROVIDED BETWEEN PRIMARY AND
 SECONDARY AND GROUNDED TO CORE.
 RATING: 75 KVA
 INSULATION CLASS: 220°C
 TEMPERATURE RISE: 150°C WINDINGS
 TERMINATIONS: ALUMINUM STUB BARS FOR AL/CU CONNECTIONS
 WEIGHT: APPX. 700 LBS.
 AGENCY APPROVALS: UL LISTED FILE # E78234
 CSA LISTED FILE # E78234

<input type="checkbox"/>	APPROVED
<input type="checkbox"/>	APPROVED WITH CHANGES
COMPANY _____	
BY _____ DATE _____	

"MEETS TP-1,1996 CLASS1 EFFICIENCY"

REF.: EN-803

REV: C	TITLE: OUTLINE FOR A 75 KVA., 1 PH., 60 HZ.		
REV: B	GENERAL PURPOSE TRANSFORMER		
REV: A			
DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.	TOLERANCES DECIMAL DIMENSIONS ±.030 FRACTIONAL DIMENSIONS ± 1/32 SCALE: DO NOT SCALE FOR DIMENSIONS ONLY	MADE BY JL	CHECKED & APPROVED
		DATE 10/30/08	
		PART NUMBER 41-1690SH	DRAWING NUMBER OUT-6268