



ELECTRICAL SPECIFICATIONS

STYLE: DRY TYPE, AIR COOLED, SINGLE PHASE, EPOXY ENCAPSULATED,
 STAINLESS STEEL ENCLOSURE, NEMA 4X
 PRIMARY VOLTAGE: 240 X 480 VOLT. 1PH
 PRIMARY TAPS: 2-2 1/2%FCAN, 2-2 1/2%FCBN
 FREQUENCY: 60HZ.
 SECONDARY VOLTAGE: 120/240 VOLT
 RATING: 5.0 KVA
 INSULATION CLASS: 180°C
 TEMPERATURE RISE: 115 °C
 SHIELD: EARTH METAL SCREEN PROVIDED BETWEEN PRIMARY AND SECONDARY
 WEIGHT: ~ 110#

REF: BR-1307
 REF: BR-1383
 REF: BR-1384
 REF: EN-870

REV: C	TITLE: OUTLINE FOR A SINGLE PHASE ISOLATION TRANSFORMER			
REV: B				
REV: A				
DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.	TOLERANCES DECIMAL DIMENSIONS ±.030 FRACTIONAL DIMENSIONS ±1/32 SCALE:	MADE BY	DATE	CHECKED & APPROVED
		JL	2/9/10	
		PART NUMBER	DRAWING NUMBER	
		85-1455SH-4X	OUT-6811	