



ELECTRICAL SPECIFICATIONS

STYLE: NEMA-3R ENCLOSED, AIR COOLED, DRY TYPE,
ENCAPSULATED, SINGLE PHASE, GENERAL PURPOSE TRANSFORMER.

PRIMARY VOLTAGE: 277 VOLTS

FREQUENCY: 60 HZ.

SECONDARY VOLTAGE: 120/240 VOLTS

RATING: 3.0 KVA.

INSULATION CLASS: 180°C

TERMINATION: LEADS

WEIGHT: 73 LBS.. APPROX.

AGENCY APPROVALS; U.L. FILE #E3210

CUL LISTED THRU UL FILE #E3210

<input type="checkbox"/>	APPROVED
<input type="checkbox"/>	APPROVED WITH CHANGES
COMPANY _____	
BY _____ DATE _____	

REF.: EN-702

REV: C	TITLE: OUTLINE FOR A 3.0KVA., 1 PH., 60 HZ.		
REV: B	GENERAL PURPOSE TRANSFORMER		
REV: A			
DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.	ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS A TOLERANCE IS NOTED NEXT TO THE DIMENSION	MADE BY JL	CHECKED & APPROVED
		PART NUMBER 85-4050SH	DRAWING NUMBER OUT-7930
		DATE 9/28/12	