



ELECTRICAL SPECIFICATIONS

STYLE: NEMA-3R ,DRY TYPE, AIR COOLED, SINGLE PHASE, EPOXY ENCAPSULATED, INDOOR-OUTDOOR, GENERAL USE, ISOLATION TRANSFORMER

PRIMARY VOLTAGE: 277 VOLTS

FREQUENCY: 60HZ.

SECONDARY VOLTAGE: 120/240 VOLTS.

SHIELD: ELECTROSTATIC SHIELD BETWEEN PRIM. & SEC.

RATED OUTPUT: 10.0 KVA.

INSULATION CLASS: 180°C

TEMPERATURE RISE: 115°C

WEIGHT:: APPX. 160 LBS

AGENCY APPROVALS: UL LISTED FILE #E3210

CUL LISTED THRU UL FILE #E3210

| | |
|--------------------------|-----------------------|
| <input type="checkbox"/> | APPROVED |
| <input type="checkbox"/> | APPROVED WITH CHANGES |
| COMPANY _____ | |
| BY _____ DATE _____ | |

EN-703

REV: C

TITLE: OUTLINE FOR 10.0 KVA. 1PH. 60HZ.

REV: B

ENCAPSULATED ISOLATION TRANSFORMER

REV: A



DONGAN ELECTRIC
MFG. CO.
PIONEER TRANSFORMER CO.

ALL DIMENSIONS ARE FOR
REFERENCE ONLY UNLESS
A TOLERANCE IS NOTED
NEXT TO THE DIMENSION

MADE BY

JL

DATE

12/20/13

CHECKED & APPROVED

PART NUMBER

85-4065SH

DRAWING NUMBER

OUT-8607