



ELECTRICAL SPECIFICATIONS

ENCLOSURE STYLE: NEMA TYPE 3R, AIR COOLED, FLOOR MOUNT, DRY TYPE,  
GENERAL PURPOSE MOTOR DRIVE TRANSFORMER

PRIMARY VOLTAGE: 575 VOLTS. 3P-3W

PRIMARY TAPS: 1-5%FCAN,1-5%FCBN

FREQUENCY:60 HZ

SECONDARY VOLTAGE: 460Y/266 VOLTS 3P-4W

SHIELD: ELECTROSTATIC SHIELD PROVIDED BETWEEN PRIMARY AND SECONDARY AND GROUNDED TO CORE.

RATING: 51.0 KVA

INSULATION CLASS: 220°C

TEMPERATURE RISE: 150°C WINDINGS

TERMINATIONS: ALUMINUM STUB BARS FOR AL/CU CONNECTIONS

WEIGHT: APPX. 500 LBS.

AGENCY APPROVALS: UL LISTED FILE # E78234

CUL LISTED THRU UL FILE # E78234

<input type="checkbox"/>	APPROVED
<input type="checkbox"/>	APPROVED WITH CHANGES
COMPANY _____	
BY _____	DATE _____

"MEETS TP-1,1996 CLASS1 EFFICIENCY"

REF.: EN-802

REV: C	TITLE: OUTLINE FOR A 51.0 KVA., 3 PH., 60 HZ.		
REV: B	GENERAL PURPOSE MOTOR DRIVE TRANSFORMER		
REV: A	REV APPROVALS-4/9/14		
<p>DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.</p>	<p>ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS A TOLERANCE IS NOTED NEXT TO THE DIMENSION</p>	MADE BY JL	DATE 11/12/13
		<p>CHECKED &amp; APPROVED</p>	