

ELECTRICAL SPECIFICATIONS

ENCLOSURE STYLE: NEMA 3R, AIR COOLED, FLOOR MOUNT, DRY TYPE,
GENERAL PURPOSE TRANSFORMER

PRIMARY VOLTAGE: 480 DELTA 3P-3W

PRIMARY TAPS: 2-2 1/2%FCAN,4-2 1/2%FCBN

FREQUENCY:60 HZ

SECONDARY VOLTAGE: 400Y/230 VOLTS 3P-4W

SHIELD: EARTH METAL SCREEN PROVIDED BETWEEN PRIMARY AND
SECONDARY AND GROUNDED TO CORE.

RATING: 75.0 KVA

INSULATION CLASS: 220°C

TEMPERATURE RISE: 150°C WINDINGS

TERMINATIONS: ALUMINUM STUB BARS FOR AL/CU CONNECTIONS

WEIGHT: 605 LBS.


AGENCY APPROVALS: UL LISTED FILE # E78234

CUL LISTED THRU UL FILE #E78234

<input type="checkbox"/>	APPROVED
<input type="checkbox"/>	APPROVED WITH CHANGES
COMPANY _____	
BY _____	DATE _____

"MEETS DOE10-II-D-431K (2016) EFFICIENCY"

REF.: EN-802

REV: C	TITLE: OUTLINE FOR A 75.0 KVA., 3 PH., 60 HZ.		
REV: B	GENERAL PURPOSE TRANSFORMER		
REV: A			
 <p>DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.</p>	<p>ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS A TOLERANCE IS NOTED NEXT TO THE DIMENSION</p>	MADE BY JL	CHECKED & APPROVED
		PART NUMBER 73-75-3494SH	DATE 6/30/16