

ELECTRICAL SPECIFICATIONS

STYLE: NEMA TYPE 3R, AIR COOLED, DRY TYPE,
THREE PHASE, GENERAL PURPOSE TRANSFORMER.

PRIMARY VOLTAGE: 380V DELTA 3P3W

FREQUENCY: 50/60 HZ.

SECONDARY VOLTAGE: 480 VOLTS, 3P3W

RATING: 30.0 KVA.

INSULATION CLASS: 220°C

TEMPERATURE RISE: 150°C

WINDINGS: ALUMINUM

TERMINATION: STUB BAR


WEIGHT: 440 LBS. APPROX.

AGENCY APPROVALS: U.L. LISTED FILE #E78234

cUL LISTED THRU UL: FILE #E78234

<input type="checkbox"/>	APPROVED
<input type="checkbox"/>	APPROVED WITH CHANGES
COMPANY _____	
BY _____ DATE _____	

REF: EN-801

REV: C	TITLE: OUTLINE FOR 30 KVA. 3PH. 50/60HZ.		
REV: B	POWER TRANSFORMER		
REV: A			
 <p>DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.</p>	<p>ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS A TOLERANCE IS NOTED NEXT TO THE DIMENSION</p>		<p>MADE BY JL</p>
			<p>DATE 4/11/14</p>
		<p>PART NUMBER 63-30-834</p>	<p>DRAWING NUMBER OUT-8763</p>