



ELECTRICAL SPECIFICATIONS

STYLE: NEMA 3R (IP23) ENCLOSED, SINGLE PHASE, NON-INHERENTLY SHORT CIRCUIT PROOF, CLASS-1, GENERAL USE, ISOLATION TRANSFORMER
 PRIMARY VOLTAGE: 190/200/208/220/380/400/416/440VOLTS.
 FREQUENCY: 50/60HZ. ± 2HZ
 SECONDARY VOLTAGE: 120/240 VOLTS.
 RATED OUTPUT: 3.0 KVA.
 INSULATION CLASS: H (200°C)
 TEMPERATURE RISE: 115°C
 AMBIENT TEMP: 60°C. MAX.
 TERMINATION: 10" LONG LEAD WIRES
 SHIELD: EARTH METAL SCREEN PROVIDED BETWEEN PRIMARY AND SECONDARY AND GROUNDED TO CORE.
 FULL LOAD REGULATION: < 2.0 %
 WEIGHT APPX: 95 POUNDS.
 AGENCY APPROVALS: UL. LISTED FILE #E3210
 CSA. LISTED FILE #E3210
 CE. DOCUMENT #EN61 558
 TUV LICENCE #R9679035

<input type="checkbox"/>	APPROVED
<input type="checkbox"/>	APPROVED WITH CHANGES
COMPANY _____	
BY _____ DATE _____	

REV: C	TITLE: OUTLINE FOR 1PH. 3.0 KVA ,50/60HZ.		
REV: B	ENCAPSULATED ISOLATION TRANSFORMER		
DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.	TOLERANCES DECIMAL DIMENSIONS ±.030 FRACTIONAL DIMENSIONS ± 1/32 DO NOT SCALE USE DIMENSIONS ONLY	MADE BY DS	DATE 7/5/05
		CHECKED & APPROVED	
		PART NUMBER ES-13250.406	DRAWING NUMBER OUT-5863