



ELECTRICAL SPECIFICATIONS

STYLE: DRY TYPE, AIR COOLED, 1 PHASE, EPOXY ENCAPSULATED,  
 CLASS 1 GENERAL USE TRANSFORMER  
 PRIMARY VOLTAGE: 190/200/208/220 X 380/400/416/440 VOLTS  
 FREQUENCY: 50/60 HZ.  
 SECONDARY VOLTAGE: 120/240 VOLTS  
 RATING: 3.0 KVA.  
 INSULATION CLASS: 200(H)°C  
 TEMPERATURE RISE: 115°C  
 SHIELD: EARTH METAL SCREEN PROVIDED BETWEEN PRIMARY AND  
 SECONDARY AND GROUNDED TO CORE.  
 AGENCY APPROVALS: UL. LISTED FILE #E3210  
 CSA CERTIFIED THROUGH UL.  
 TUV LICENCE #R9679035  
 CE. DOCUMENT #EN60742

<input type="checkbox"/>	APPROVED
<input type="checkbox"/>	APPROVED WITH CHANGES
COMPANY _____	
BY _____ DATE _____	

REF.: EN-687

REV: C	TITLE: OUTLINE FOR A 3.0KVA., 1PH., 50/60 HZ.			
REV: B	CLASS 1 GENERAL USE TRANSFORMER			
REV: A				
DONGAN ELECTRIC MFG. CO.  PIONEER TRANSFORMER CO.	TOLERANCES DECIMAL DIMENSIONS ±.030 FRACTIONAL DIMENSIONS ± 1/32  SCALE: DO NOT SCALE FOR DIMENSIONS ONLY	MADE BY	DATE	CHECKED & APPROVED
		JL	3/13/09	
		PART NUMBER	DRAWING NUMBER	
		ES-11250.406	OUT-6468	