



**ELECTRICAL SPECIFICATIONS**

STYLE: OPEN STYLE, AIR COOLED, SINGLE PHASE, NON-INHERENTLY SHORT CIRCUIT PROOF, GENERAL USE, ISOLATION TRANSFORMER

PRIMARY VOLTAGE: 380/416/480 VOLTS.

FREQUENCY: 50/60HZ.

SECONDARY VOLTAGE: 24/120 VOLTS. MAX CURRENT @24V:9A TOTAL RATING NOT TO EXCEED 1 KVA  
 RATED OUTPUT: 1.0 KVA.

INSULATION CLASS: H (200°C)

TEMPERATURE RISE: 115°C

TERMINATION: FINGER SAFE TERMINALS.

SHIELD: EARTH METAL SCREEN PROVIDED BETWEEN PRIMARY AND SECONDARY AND GROUNDED TO CORE.

WEIGHT APPX: 30 POUNDS.

AGENCY APPROVALS: U.L. LISTED FILE #E3210

CSA LISTED THRU U.L. FILE #E3210

CE DOCUMENT #EN 60 742

TUV LICENSE #R9679035

REV: C	TITLE: OUTLINE FOR 1.0 KVA. 1PH. 50/60HZ.		
REV: B	GENERAL USE ISOLATION TRANSFORMER		
REV: A			
DONGAN ELECTRIC MFG. CO.  PIONEER TRANSFORMER CO.	TOLERANCES DECIMAL DIMENSIONS ±.030 FRACTIONAL DIMENSIONS ±1/32	MADE BY JL	DATE 1/7/09
		CHECKED & APPROVED	
		PART NUMBER ES-10200.366	DRAWING NUMBER OUT-6402