



ELECTRICAL SPECIFICATIONS

STYLE: OPEN STYLE, AIR COOLED, SINGLE PHASE, NON-INHERENTLY
 SHORT CIRCUIT PROOF, GENERAL USE, ISOLATION TRANSFORMER
 PRIMARY VOLTAGE: 380/400/416 VOLTS.
 FREQUENCY: 50/60HZ. +/- 1HZ
 SECONDARY VOLTAGE: 110/115/120/220/230/240 VOLTS.
 RATED OUTPUT: 3.0 KVA.
 INSULATION CLASS: H (200°C)
 TEMPERATURE RISE: 115°C
 TERMINATION: FINGER SAFE TERMINALS.
 SHIELD: EARTH METAL SCREEN PROVIDED BETWEEN PRIMARY AND
 SECONDARY AND GROUNDED TO CORE.
 REGULATION: 2.3%
 EFFICIENCY: 95.5%
 WEIGHT APPX: 60 POUNDS.
 AGENCY APPROVALS: U.L. LISTED FILE #E3210
 CSA LISTED THRU U.L. FILE #E3210
 CE DOCUMENT #EN 60 742
 TUV LICENSE #R9679035

REV: C	TITLE: OUTLINE FOR 3.0 KVA. 1PH. 50/60HZ.		
REV: B	GENERAL USE ISOLATION TRANSFORMER		
A			
DONGAN ELECTRIC MFG. CO. PIONEER TRANSFORMER CO.	TOLERANCES DECIMAL DIMENSIONS ±.030 FRACTIONAL DIMENSIONS ±1/32 <i>N.T.S.</i>	MADE BY	CHECKED & APPROVED
		M.JAFRI	12-12-97
		PART NUMBER	DRAWING NUMBER
		ES-10250.376	OUT-3100